



3/8-16 thread x 0.75" min deep
 (4) Holes equispaced on $\varnothing 5.875"$ B.C.

(3) Holes - #8-32
 equispaced as shown
 on 3.687" B.C.
 (EndCover Mounting Holes)

Model	Length "L" Max
TT-4203	11.68" (297)
TT-4204	12.68" (322)
TT-4205	13.68" (347)
TT-4206	14.68" (373)
TT-4207	15.68" (398)
TT-4208	16.68" (424)
TT-4209	17.68" (449)

Notes:-

1. With a positive current applied to pin C with respect to pin D, rotation shall be clockwise facing mounting end of motor. With this rotation a positive voltage shall be generated on pin J of tach with respect to pin K.
2. Motor can be mounted in any position
3. Thermostat set to open at $90^{\circ}\text{C} \pm 6^{\circ}\text{C}$ & close at $70^{\circ} \pm 6^{\circ}\text{C}$ falling. N.C. contacts rated to 3.0 Amps, 250V. AC., pins A & F
4. All dimensions in inches with mm in ().

				Tolerances. X.XX = ± 0.015 X.XXX = ± 0.005 Ang. Dim. = $\pm 1^{\circ}$		Scale : NTS		Weight :
				Date	Name	Material : SEE NOTES Remove all burrs and sharp corners		
				Drawn	25/11/05	Motor Outline		
				App'd		TT 420X-1011		
Issue	ECO. No.	Date	Name	App'd	Norm	TT 420X-1011		
bobby servo-electronic ag						TT 420X-1011		
						Sheet 1 of 1		